



OR

- 6 a. Define gyroscopic effect. With usual notations and diagram, derive an expression for the gyroscopic couple produced by a rotating disc. (08 Marks)
- b. An aeroplane has engine speed 2000rpm clockwise when viewed from rear. It is flying at 240 kmph speed and turns towards left and completes a quarter circle of 60m radius. The mass of the rotor engine and the propeller of the plane is 450kg with a radius of gyration of 320 mm. Determine the gyroscopic couple on the aircraft and its effect. In what way the effect changes when the (i) Aeroplane turns towards right (ii) Engine rotates clockwise when viewed from the front (nose end) and the aeroplane turns right. (12 Marks)

**Module-4**

- 7 a. Define the following terms:  
 (i) Simple harmonic motion (ii) Natural frequency (iii) Resonance  
 (iv) Forced vibration (v) Phase difference (10 Marks)
- b. Find the natural frequency of the following system shown in Fig.Q7(b). (10 Marks)




Fig.Q7(b)

OR

- 8 a. Set up the differential equation for a spring mass damper system and obtain complete solution for the over-damped system. (10 Marks)
- b. A vibrating system consists of mass 25kg, a spring of stiffness 15 kN/m and a Damper. The damping provided is only 15% of critical value. Determine (i) Critical damping coefficient (ii) Damping factor (iii) Natural frequency (iv) Logarithmic decrement (v) Ratio of two consecutive amplitudes of vibration. (10 Marks)

**Module-5**

- 9 a. Define transmissibility and derive an expression for the transmissibility ratio and the phase angle for the transmitted force. (10 Marks)
- b. A mass of 100 kg has been mounted on a spring-dash pot system having spring stiffness of 19600 N/m and damping coefficient 100 N-sec/mt. The mass acted upon by a harmonic force of 39N at the undamped natural frequency of the system; find  
 (i) Amplitude of vibration of the mass  
 (ii) Phase difference between the force and displacement  
 (iii) Force transmissibility ratio. (10 Marks)

OR

- 10 a. Derive an expression for magnification factor or amplitude ratio for spring mass system with viscous damping subjected to harmonic force. (10 Marks)
- b. A 54 N weight is suspended by a spring with a stiffness of 1100 N/m. It is forced to vibrate by a harmonic force of 5 N. Take viscous damping of 77 N-s/m and find,  
 (i) Resonant frequency (ii) Amplitude at resonance (iii) Phase angle at resonance.  
 (iv) Damped natural frequency (v) Frequency at which maximum amplitude of vibration occurs (vi) Maximum or Peak amplitude (vii) Phase angle corresponding to peak amplitude (viii) Speed at which maximum amplitude of vibration would occur. (10 Marks)

\*\*\*\*\*